



ELECTRODE STRUCTURE FOR ELECTRON GUN

CROSS-REFERENCE OF RELATED APPLICATIONS

This application claims the benefit of French patent application
5 serial no. 9901628 filed February 11, 1999, which is hereby incorporated
herein by reference, and which claims the benefit under 35 U.S.C. § 365 of
International Application PCT/EP00/01131, filed February 11, 2000, which
was published in accordance with PCT Article 21(2) on August 17, 2000 in
English.

10 FIELD OF THE INVENTION

The invention relates to an electron gun for cathode-ray tube and
more particularly to the manner of making certain electrodes which extend
along the path of the electron beams in the direction of the screen of the
tube.

15 BACKGROUND OF THE INVENTION

In an electron gun for cathode-ray tubes, a few components are of
elongate shape in the direction of the beam or beams generated by one or
more cathodes. The objective of these elongate shapes is to form said
beams or to make them converge towards the screen of the tube. The first
20 electrode of the gun, also referred to as the control electrode, may also be
of elongate shape and surround the cathode or cathodes more or less
totally. In this case, the elongate shape allows confinement of the energy
dissipated by the cathode filaments so as to render the latter emissive and
thereby increase the energy yield of the assembly.

25 The control electrode G1, drilled with one or more orifices for the
passage of the electron beams, may be made by deep drawing, in such a
way as to make the electrode surface and its lateral skirt from one plane
component. Such an electrode G1 is for example illustrated by the Dutch
patent application 8103395. It is also possible to make the electrode G1
30 by welding, onto the plane part drilled with orifices, a lateral skirt obtained
by bending. These methods have shown their limitations since the
subsequent adjusting of the cathode modules can only be done readily if

the shape and final dimensions of the electrode G1 are perfectly controlled and in accordance with those specified. The methods of the prior art do not enable the shape of the electrode G1 to be controlled with sufficient accuracy.

5 SUMMARY OF THE INVENTION

The electron gun according to the invention affords a solution to this problem. It comprises at least one cathode for emitting an electron beam, a dish-shaped control electrode G1, comprising a substantially plane part provided with at least one aperture for the passage of the electron beam
10 emanating from the cathode and a skirt at least partially surrounding the cathode, means for supporting the cathode so as to keep the latter at a specified distance from the electrode G1, characterized in that the control electrode G1 comprises at least three separate metal components:

- a substantially plane component drilled with apertures which are
15 intended to face each cathode,
- at least two metal components forming the lateral skirt at least partially surrounding the cathode, the two components being secured to one another as well as to the plane part, for example by welding.

Moreover, the invention has the advantage of allowing the
20 modification of any electron gun comprising a plane control electrode G1 by the addition of a structure made from two components so as to form a lateral skirt for confinements which did not exist in the starting electrode G1, doing so without modifying the shape of the initial electrode.

BRIEF DESCRIPTION OF THE DRAWINGS

25 The invention will be better understood with the aid of the description and of the drawings below in which:

- Figure 1 is a cathode ray tube according to the invention;
- Figure 2 shows an exploded view of the rear part of a tube
incorporating a gun according to the prior art;
- 30 - Figure 3 illustrates a mode of making a dish-shaped electrode G1 by deep drawing according to the prior art;

- Figure 4 is a section through the bottom part of the electron gun according to the prior art;

- Figure 5 is an exploded view of an embodiment of the invention including the electrode G1 and the cathode supports; and

5 - Figure 6 shows in perspective an electrode G1 according to the invention.

DETAILED DESCRIPTION

As illustrated by Figure 1, a color cathode-ray tube 1 comprises a front face 2 onto which are deposited networks of luminescent materials 10
10 intended for reproducing a colored image under the impact of electron beams 6, 7, 8 generated by an electron gun 5. A color selection mask 11, drilled with holes 12, is interposed between the gun and the front face so that each electron beam illuminates only the parts corresponding thereto on the screen. A system 13 for deflecting the electron beams is arranged
15 on the neck 4 of the tube so that the beams 6, 7, 8 sweep the whole of the screen 10.

Figure 2 shows an electron gun according to the prior art in greater detail. This gun 5 comprises three cathodes, a central cathode 22 and two lateral cathodes 21, a dish-shaped electrode G1 25, and a succession of
20 electrodes 26, 27, 28 etc. The electrodes are drilled with holes to allow the passage of the electron beams 6, 7, 8. The electrodes are secured to one another by virtue of glass beads 29 into which are inserted metal parts 20 of said electrodes.

Figure 3 illustrates a mode of making an electrode G1 by deep
25 drawing according to the prior art. The electrode 25 consists of a plane face 40 drilled with holes 44, 43 for the passage of the electron beams and of a lateral skirt 41 substantially perpendicular to the plane part 40. Metal parts 42 project for insertion into the beads 29.

Figure 4 shows a section through the cathode/G1 assembly of
30 Figure 3, in a plane parallel to the longitudinal axis Z of the tube, level with a lateral orifice 43 of G1.

The cathode 50 possesses means of support 55, 56 inside G1, which are insulated from G1 by parts 52 made for example of ceramic. A filament 51 for heating the cathode is supplied electrically with the aid of conductors 53 linked to rigid terminals 54. The means of support 55 are
5 welded to the skirt 41 of the electrode so as to secure the cathode to G1. The cathode or cathodes must be secured to the electrode G1 in such a way that the position of each cathode and its distance from the hole in G1 corresponding thereto is very accurately fixed. If the shapes and dimensions of the electrode G1 do not correspond accurately to the
10 nominal shapes and dimensions, it will not be possible for the welding of the cathode modules inside the dish to be performed accurately; this will for example result in the surface of the cathode 50 not being arranged perfectly facing the aperture 43, in the surface 40 bearing the apertures 43, 44 being deformed by the mechanical stress exerted by the welding of the
15 supports 55 because the dimensions do not correspond perfectly. These problems may be engendered by the difficulty of making the component G1 by deep drawing, a method which, in mass production, does not allow the geometrical dimensions to be controlled with sufficient accuracy.

It is known moreover to make a dish-shaped G1 by welding a lateral
20 skirt 41 onto a plane electrode surface 40. The surface of G1 containing the orifices 43, 44 is a surface whose geometry is highly critical since it acts directly in the zone of formation of the electron beam or beams. The end part of the skirt should have a geometry which is defined perfectly so as to fit the surface of the plane part 40 to which it is intended to be
25 welded, otherwise it will give rise to mechanical stresses which will modify the nominal shapes and dimensions of G1. This is what generally occurs when the skirt 41 is an annular flange.

The present invention proposes a structure for making an electrode skirt allowing said skirt to be fitted without mechanical stress to any type of
30 substantially plane electrode.

Figure 5 shows an exploded view of an electrode G1 and cathode supports according to the invention. The electrode 25' possesses a

substantially plane part 61 drilled with apertures to allow the passage of the electron beams emanating from the cathodes. The ends 63 are intended to be inserted into glass beads ensuring the rigidity of the gun and the relative positioning of its constituent electrodes. The cathode supports comprise a first skirt 56' surrounding the cathode and its filament, tabs 55' insulated from the skirt by a ceramic annulus 52, and rigid terminals 54 for receiving the filament supply wires. Two components 60, 66 secured to one another, for example by welding, form a skirt which surrounds the cathode supports; the skirt 60, 66 may either surround a single cathode module or the assembly of three modules in the case of in-line guns for color cathode-ray tube; the cathode supports and the skirt 60, 66 are secured for example by welding the tabs 55 to said skirt 60, 66, the assembly is then secured to the electrode G1 by welding the periphery 62 of the skirt 60, 66 to said electrode.

Figure 6 shows in perspective the electrode G1 made from three metal components: the substantially plane surface of electrode 61 drilled with apertures 44', 43' and the two components of the skirt 60, 66 which are welded together level with their end 67 overlap; the geometry of the periphery 62 of 60, 66 is tailored in such a way as to come into stress-free contact with the substantially plane surface of 61. The cathode modules are subsequently inserted into this assembly and welded to the skirt 60, 66.

By having a skirt 60, 66 consisting of at least two components 60 and 66, it is possible to achieve tailored positioning of the periphery 62 of the skirt 60, 66 intended to come into contact with the surface of the component 61, to which surface it will be welded. Regarding the Z axis as the principal axis of the tube, the X axis parallel to the direction of alignment of the holes 43', 44' and the Y axis perpendicular to X, the positioning of 60 with respect to 66 is achieved by a parting of the two components along the direction Y and a positioning along Z tailored in such a way that the periphery 62 mates, without mechanical stress, with

the surface of the component 61. The assembly is secured by welding the ends 67 which therefore overlap at least partially.

The principle may be extended in a simple manner to a skirt consisting of more than two separate components. In this way, it is possible to modify the geometry and the dimensions of the cathode and of its supports without having to modify the plane part 61, bearing the orifices 43', 44'. This part 61 has very tight tolerances, owing to the fact that its geometry determines the electron optics of the gun in the zone of formation of the beam or beams; this results in a saving when tailoring new cathode modules to an existing electrode G1 both in terms of design of the component and the tools for manufacturing said component.

In an advantageous embodiment, the two parts 60 and 66 are of strictly identical geometry and dimension. This makes it possible both to reduce the manufacturing costs and to obtain easier management of the stock of components, the electrode G1 then consisting of only two different types of components.

The invention can be adapted to the making of any type of electrode comprising a plane part of highly critical geometry and a cylindrical part which extends along the Z direction for a considerable length, that is to say over a length equal to at least five times the thickness of the plane part, a structure which makes deep-drawing unsuitable for application to electron gun electrodes.